L19	35	17 and (rout$3 or path) with reflect$3	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:38
L20	3	17 and route with reflection	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:38
L21	773	15 and (path$3 or rout$3) with destination	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:39
L22	1	21 and equal with minimum	USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:40
L23	47	(border with gateway with protocol) and (autonomous with system) with (path$3 or rout$3) with destination	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 15:05

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L3	105	(internal with BGP)	US-PGPUB; USPAT; EPO; IBM_TDB	OR	OFF	2006/01/14 14:31
L4	105	(internal with BGP)	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 13:15
L5	11	4 and rout$3 with reflect$3	USPAT	OR	OFF	2006/01/14 13:06
L6	11	(internal with BGP) and (multi with exit with discriminator)	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:43
L7	82	(internal with BGP) and (path$3 or rout$3) with destination	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:22
L8	97	(internal with BGP) and internet	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:22
L9	26	8 and border with gateway	USPAT	OR	OFF	2006/01/14 14:22
L10	86	8 and border with gateway	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:22
L13	21	10 and route with reflect$3	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:23
L14	10	10 and route with reflect$3 and mesh	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:23
L15	1014	((internal with BGP) or (border with gateway with protocol))	US-PGPUB; USPAT; EPO; IBM_TDB	OR	OFF	2006/01/14 14:43
L16	61	15 and (multiple or plural$8) with (path$3 or rout$3) with destination	USPAT	OR	OFF	2006/01/14 14:33
L17	169	15 and (multiple or plural$8) with (path$3 or rout$3) with destination	US-PGPUB; USPAT; EPO; IBM_TDB	OR	ON	2006/01/14 14:39
L18	11	17 and (rout$3 or path) with reflect$3	USPAT	OR	OFF	2006/01/14 14:35